

**TEXTILE BRAID****870AA****FLEXOR 3****SAE 100 R3 - EN 854 R3**

<b>Tube</b>	OIL RESISTANT SYNTHETIC RUBBER
<b>Reinforcement</b>	Two high tensile textile braids and two tensile steel braids
<b>Cover</b>	ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER
<b>Application</b>	MEDIUM PRESSURE HYDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER.
<b>Constant operation</b>	-40°C +100°C (T max air = +70°C)
<b>Ambient temperature</b>	-40°C +80°C
<b>Fittings</b>	Consult fittings catalogue
<b>Length</b>	Random
<b>Branding</b>	ALFAGOMMA FLEXOR 3 ID... - WP ... MPa (... PSI) - SAE 100R3- EN854 R3-DN ... - Q/yr
<b>Note</b>	S.F.: 4:1

Code	ID mm	ID in	Dash	OD mm	OD in	WP Mpa	WP psi	BP Mpa	BP psi	BR mm	BR in	Weight kg/m	Weight lb/C ft
870AA00600YXA8	6	1/4	-4	14,3	0,56	8,6	1250	35	5000	76	3	0,18	12
870AA00800YXA8	8	5/16	-5	17,5	0,69	8,3	1200	33	4800	102	4,1	0,24	16
870AA01000YXA8	10	3/8	-6	19,1	0,75	7,8	1125	31	4500	102	4,1	0,25	17
870AA01200YXA8	13	1/2	-8	23,8	0,94	7	1000	28	4000	127	5,1	0,38	25
870AA01600YXA8	16	5/8	-10	27	1,06	6	875	24	3500	140	5,6	0,46	31
870AA02000YXA8	19	3/4	-12	31,8	1,25	5,2	750	21	3000	152	6,1	0,63	42
870AA02500YXA8	25	1	-16	38,1	1,5	3,9	565	16	2260	203	8,1	0,76	51
870AA03245YXA8	32	1.1/4	-20	45	1,77	2,6	377	10	1508	254	10,2	0,94	63