

806AA
FLEXOR 6
SAE 100 R6 - EN 854 R6


Tube	OIL RESISTANT SYNTHETIC RUBBER
Reinforcement	ONE HIGH TENSILE TEXTILE BRAID
Cover	ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER
Application	LOW PRESSURE HIDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER. SPECIALLY DESIGNED FOR USE IN "PUSH ON" APPLICATIONS
Constant operation	-40°C +100°C (T max air = +70°C)
Ambient temperature	-40°C +80°C
Fittings	Consult fittings catalogue
Length	Random
Branding	ALFAGOMMA FLEXOR 6 ID... - WP ... MPa (... PSI) - SAE 100R6-EN854 R6 -DN ... - Q/yr
Note	* Alfagomma proprietary hose Not listed in SAE J517 100 R6 spec. S.F.: 4:1

Code	ID mm	ID in	Dash	OD mm	OD in	WP Mpa	WP psi	BP Mpa	BP psi	BR mm	BR in	Weight kg/m	Weight lb/C ft
806AA006008JA8	6	1/4	-4	12,7	0,5	2,8	400	11	1600	64	2,6	0,13	9
806AA008008JA8	8	5/16	-5	14,3	0,56	2,8	400	11	1600	76	3	0,13	9
806AA010008JA8	10	3/8	-6	15,9	0,63	2,8	400	11	1600	76	3	0,17	11
806AA012008JA8	13	1/2	-8	19,8	0,78	2,8	400	11	1600	102	4,1	0,23	15
806AA016008JA8	16	5/8	-10	23	0,91	2,4	350	10	1400	107	4,3	0,27	18
806AA020008JA8	19	3/4	-12	26,9	1,06	2,1	300	8	1200	152	6,1	0,37	25
806AA025008JA8*	25	1	-16	33,4	1,31	1,7	250	7	1000	203	8,1	0,49	33