

S-470 OO
GENERAL PURPOSE FOOD QUALITY S & D - PVC
FDA 90/128/EC A+B+C AS 2070


TUBE	TRASPARENT PVC - ABRASION AND OZONE RESISTANT
REINFORCEMENT	STEEL HELIX WIRE
COVER	
APPLICATION	GENERAL PURPOSE LIQUID FOOD AND ALCOHOLIC BEVERAGES SUCTION AND DELIVERY -MAX 28% PROOF. STERILIZE WITH 5% SODA SOLUTION.
SAFETY FACTOR	3:1
TEMPERATURE	-5°C +60°C (+23°F +140°F)
BRAND TEXT	ALFAGOMMA - ITALY - S-470 - GENERAL PURPOSE FOOD QUALITY S&D-(logo) -lotto
BRAND TYPE	BLACK LETTERS
APPROVALS	IANESCO
NOTE	

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
470OO010164LK0	10	3/8	16	3	170	15	225	90	40	60	60
470OO013194LK0	13	1/2	19	3	205	7	100	85	52	60	60
470OO014204LK0	14	9/16	20	3	220	6	90	85	56	60	60
470OO016224LK0	16	5/8	22	3	250	6	90	85	64	60	60
470OO018264LK0	18	23/32	26	3,5	320	6	90	85	72	60	60
470OO020284LK0	20	13/16	28	3,5	340	5	75	85	80	60	60
470OO022304LK0	22	7/8	30	3,5	380	5	75	85	88	60	60
470OO025334LK0	25	1"	33	4	530	5	75	85	100	60	60
470OO030384LK0	30	1" 3/16	38	4	620	4	60	85	120	60	60
470OO032404LK0	32	1" 1/4	40	4	655	4	60	85	128	60	60
470OO035454LK0	35	1" 3/8	45	4,5	800	4	60	85	140	50	50
470OO038484LK0	38	1" 1/2	48	4,5	855	4	60	85	152	50	50
470OO040504LK0	40	1" 9/16	50	4,5	895	3	45	85	160	50	50
470OO045554LK0	45	1" 3/4	55	5	1100	3	45	80	180	50	50
470OO051614LK0	51	2"	61	5	1230	3	45	80	204	50	50
470OO060724LK0	60	2" 3/8	72	6	1700	2	30	80	240	50	50
470OO063754LK0	63	2" 1/2	75	6	1775	2	30	80	252	50	50
470OO070844LK0	70	2" 3/4	84	7	2030	2	30	80	280	50	50
470OO076904LK0	76	3"	90	7	2450	2	30	70	304	50	50
470OO080944LK0	80	3" 1/8	94	7	2565	2	30	70	320	50	50
470OO090044LK0	90	3" 1/2	104	7	3000	2	30	70	360	50	50
470OO102164LK0	102	4"	116	7	3480	2	30	70	408	50	50
470OO105214LK0	105	4" 1/8	121	8	4250	3	45	90	420		