

Hot Water & Steam

T-352 AA

RADIATOR 5 BAR (75 PSI)

EXCEEDS DIN 73411



TUBE	BLACK EPDM
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS
COVER	BLACK EPDM - HEAT, ABRASION AND OZONE RESISTANT
APPLICATION	RADIATOR.
SAFETY FACTOR	3:1
TEMPERATURE	-40°C +120°C (-40°F +248°F)
BRAND TEXT	ALFAGOMMA -ITALY- T-352 RADIATOR -DIN 73411- dia mm
BRAND TYPE	YELLOW TRANSFER
APPROVALS	
NOTE	

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
352AA013213WD0	13	1/2	21	4	280	5	75			1/61	1
352AA016243WD0	16	5/8	24	4	330	5	75			1/61	1
352AA018263WD0	18	23/32	26	4	360	5	75			1/61	1
352AA020283WD0	20	13/16	28	4	390	5	75			1/61	1
352AA022303WD0	22	7/8	30	4	420	5	75			1/61	1
352AA025333WD0	25	1"	33	4	470	5	75			1/61	1
352AA028363WD0	28	1" 1/8	36	4	510	5	75			1/61	1
352AA030383WD0	30	1" 3/16	38	4	550	5	75			1/61	1
352AA032403WD0	32	1" 1/4	40	4	580	5	75			1/61	1
352AA035433WD0	35	1" 3/8	43	4	620	5	75			1/61	1
352AA038483WD0	38	1" 1/2	48	5	850	5	75			1/61	1
352AA040503WD0	40	1" 9/16	50	5	890	5	75			1/61	1
352AA042523WD0	42	1" 5/8	52	5	930	5	75			1/61	1
352AA045553WD0	45	1" 3/4	55	5	990	5	75			1/61	1
352AA048583WD0	48	1" 7/8	58	5	1040	5	75			1/61	1
352AA051613WD0	51	2"	61	5	1110	5	75			1/61	1
352AA055653WD0	55	2" 1/6	65	5	1190	5	75			1	1
352AA057673WD0	57	2" 1/4	67	5	1230	5	75			1	1
352AA060703WD0	60	2" 3/8	70	5	1280	5	75			1/61	1
352AA063733WD0	63	2" 1/2	73	5	1340	5	75			1	1
352AA070803WD0	70	2" 3/4	80	5	1440	5	75			1	1
352AA076863WD0	76	3"	86	5	1550	5	75			1	1
352AA080903WD0	80	3" 1/8	90	5	1630	5	75			1	1
352AA090023WD0	90	3" 1/2	102	6	2020	5	75			1	1
352AA102143WD0	102	4"	114	6	2260	5	75			1	1
352AA110223WD0	110	4" 5/16	122	6	2420	5	75			1	1