

**T-330 AH**  
**SATURATED STEAM 17 BAR (250 PSI) - STEEL**  
**REINFORCED**  
**NFT 47263/I3 BS 5342/2A DIN 2825**



<b>TUBE</b>	BLACK EPDM
<b>REINFORCEMENT</b>	HIGH TENSILE STEEL CORDS
<b>COVER</b>	RED EPDM - HEAT, ABRASION AND OZONE RESISTANT - PIN PRICKED
<b>APPLICATION</b>	SATURATED STEAM.
<b>SAFETY FACTOR</b>	10:1
<b>TEMPERATURE</b>	-40°C +210°C (-40°F +410°F)
<b>BRAND TEXT</b>	ALFAGOMMA -ITALY- T-330 17 BAR (250 PSI) STEAM - DRAIN AFTER USE- BS 5342/A/2-NFT47263 CI T3 DIN2825 q/yy
<b>BRAND TYPE</b>	EMBOSSSED
<b>APPROVALS</b>	
<b>NOTE</b>	DIAM. 63mm AND 76mm NOT COVERED BY ABOVE MENTIONED NORMS

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
330AH010223YA3	10	3/8	22	6	490	17	250	100	61		61
330AH013253YA3	13	1/2	25	6	560	17	250	130	15,25/30,5/61		61
330AH016283YA3	16	5/8	28	6	620	17	250	160	61		61
330AH019323YA3	19	3/4	32	6,5	730	17	250	190	15,25/30,5/61		61
330AH019333YA3	19	3/4	33	7	850	17	250	190	61		
330AH025383YA3	25	1"	38	6,5	900	17	250	250	15,25/30,5/61		61
330AH025403YA3	25	1"	40	7,5	1040	17	250	250	61		
330AH032463YA3	32	1" 1/4	46	7	1320	17	250	320	61		61
330AH032483YA3	32	1" 1/4	48	8	1500	17	250	320	61		
330AH038523YA3	38	1" 1/2	52	7	1540	17	250	380	61		61
330AH038543YA3	38	1" 1/2	54	8	1740	17	250	380	61		
330AH051673YA3	51	2"	67	8	2150	17	250	510	61		61
330AH051693YA3	51	2"	69	9	2400	17	250	510	61		
330AH063833YA3	63	2" 1/2	83	10	3720	17	250	630	30,5		30,5
330AH076963YA3	76	3"	96	10	4410	17	250	760	30,5		30,5