

T-155 AA
COMPRESSED AIR 20 BAR (300 PSI) - HEAVY DUTY



TUBE	BLACK SBR/NBR - OIL MIST RESISTANT
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS
COVER	BLACK SBR - ABRASION AND OZONE RESISTANT
APPLICATION	COMPRESSED AIR DESIGNED FOR HEAVY DUTY APPLICATIONS.
SAFETY FACTOR	<= 51mm 3:1 >= 55mm 2.5:1
TEMPERATURE	-30°C +80°C (-22°F +176°F)
BRAND TEXT	ALFAGOMMA -ITALY- T-155 20 BAR (300 PSI) AIR
BRAND TYPE	BLUE LETTERS
APPROVALS	
NOTE	

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
155AA019291GF0	19	3/4	29	5	540	20	300			20/30,5/40	40
155AA022321GF0	22	7/8	32	5	610	20	300			20	20
155AA025351GF0	25	1"	35	5	680	20	300			20/30,5/40	40
155AA028381GF0	28	1" 1/8	38	5	780	20	300			20	20
155AA030421GF0	30	1" 3/16	42	6	1010	20	300			20	20
155AA032441GF0	32	1" 1/4	44	6	1060	20	300			20/30,5/40	40
155AA035471GF0	35	1" 3/8	47	6	1140	20	300			20	20
155AA038501GF0	38	1" 1/2	50	6	1240	20	300			20/30,5/40	40
155AA040521GF0	40	1" 9/16	52	6	1290	20	300			20/40	40
155AA045571GF0	45	1" 3/4	57	6	1440	20	300			20	20
155AA051651GF0	51	2"	65	7	1630	20	300			20/30,5/40	40
155AA055691GF0	55	2" 1/6	69	7	1730	20	300			30,5	30,5
155AA060761GF0	60	2" 3/8	76	8	2160	20	300			20	20
155AA063791GF0	63	2" 1/2	79	8	2250	20	300			20/30,5	20
155AA076921GF0	76	3"	92	8	2750	20	300			20/30,5	20
155AA090061GF0	90	3" 1/2	106	8	3180	20	300			20	20
155AA102181GF0	102	4"	118	8	3600	20	300			20/30,5	20
155AA152701GF0	152	6"	170	9	6100	20	300				