

Water & Liquids

T-203 AA

WATER S&D 10 BAR (150 PSI)



TUBE	BLACK SBR
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
COVER	BLACK SBR - ABRASION AND OZONE RESISTANT
APPLICATION	WATER SUCTION AND DELIVERY.
SAFETY FACTOR	<= 127mm 3:1 152-254mm 2.5:1 305mm 1.5:1
TEMPERATURE	-30°C +80°C (-22°F +176°F)
BRAND TEXT	ALFAGOMMA -ITALY- T-203 10 BAR (150 PSI) WATER S&D
BRAND TYPE	GREEN LETTERS

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
203AA025352OE0	25	1"	35	5	800	10	150	100	100	20/30,5/40	40
203AA030402OE0	30	1" 3/16	40	5	910	10	150	100	120	40	40
203AA032422OE0	32	1" 1/4	42	5	960	10	150	100	128	20/30,5/40	40
203AA035452OE0	35	1" 3/8	45	5	1030	10	150	100	140	40	
203AA038482OE0	38	1" 1/2	48	5	1110	10	150	100	152	20/30,5/40	40
203AA040502OE0	40	1" 9/16	50	5	1160	10	150	100	160	40	40
203AA045552OE0	45	1" 3/4	55	5	1290	10	150	100	180	40	40
203AA051612OE0	51	2"	61	5	1440	10	150	100	204	20/30,5/40	40
203AA060722OE0	60	2" 3/8	72	6	1840	10	150	100	240	20	20
203AA063752OE0	63	2" 1/2	75	6	1920	10	150	90	252	20/30,5	20/30,5
203AA070822OE0	70	2" 3/4	82	6	2120	10	150	90	280	20	20
203AA076882OE0	76	3"	88	6	2290	10	150	90	304	20/30,5	20/30,5
203AA080922OE0	80	3" 1/8	92	6	2470	10	150	90	320	20	20
203AA090022OE0	90	3" 1/2	102	6	2860	10	150	90	360	20/30,5	20
203AA102142OE0	102	4"	114	6	3200	10	150	90	408	20/30,5	20/30,5
203AA110222OE0	110	4" 5/16	122	6	3420	10	150	80	440	20	20
203AA115272OE0	115	4" 1/2	127	6	3560	10	150	80	460	30,5	
203AA120342OE0	120	4" 3/4	134	7	4770	10	150	80	600	20	20
203AA127412OE0	127	5"	141	7	5020	10	150	80	635	6,1	6,1
203AA152662OE0	152	6"	166	7	6250	10	150	80	760	6,1/20	6,1
203AA203212OE0	203	8"	221	9	10580	10	150	70	1015	6,1/10/15,25	6,1
203AA254722OE0	254	10"	272	9	14390	10	150	60	1270	6,1	
203AA305272OE0	305	12"	327	11	20980	10	150	60	1550	6,1	