

## Acid, Chemical &amp; Multipurpose

## T-202 AA

## GENERAL PURPOSE S&amp;D 10 BAR (150 PSI) - EPDM



<b>TUBE</b>	BLACK EPDM
<b>REINFORCEMENT</b>	HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
<b>COVER</b>	BLACK EPDM - ABRASION AND OZONE RESISTANT
<b>APPLICATION</b>	MILD CHEMICALS AND FERTILIZERS SUCTION AND DELIVERY IN GENERAL INDUSTRIAL AND AGRICULTURAL APPLICATIONS. REFER TO CHEMICAL RESISTANCE CHART.
<b>SAFETY FACTOR</b>	<= 127mm 3:1 >=152mm 2.5:1
<b>TEMPERATURE</b>	-30°C +80°C (-22°F +176°F)
<b>BRAND TEXT</b>	ALFAGOMMA -ITALY- T-202 10 BAR (150 PSI) GENERAL PURPOSE - EPDM
<b>BRAND TYPE</b>	GREEN LETTERS

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
202AA025352OB0	25	1"	35	5	680	10	150	100	100	30,5/61	
202AA032422OB0	32	1" 1/4	42	5	810	10	150	100	128	30,5/61	
202AA038482OB0	38	1" 1/2	48	5	930	10	150	100	152	30,5/61	
202AA051612OB0	51	2"	61	5	1220	10	150	100	204	30,5/61	
202AA063752OB0	63	2" 1/2	75	6	1760	10	150	90	252	30,5/61	
202AA076882OB0	76	3"	88	6	2100	10	150	90	304	30,5/61	
202AA090022OB0	90	3" 1/2	102	6	2640	10	150	90	360	30,5	
202AA102142OB0	102	4"	114	6	2950	10	150	90	408	30,5/61	
202AA127412OB0	127	5"	141	7	4670	10	150	80	635	6,1/15,25/30,5	
202AA152662OB0	152	6"	166	7	5840	10	150	80	760	6,1/7,625/15,25/30,5	
202AA203212OB0	203	8"	221	9	9810	10	150	70	1015	6,1/7,625/10	