

**L-185 AA**  
**COMPRESSED AIR 20 BAR (300 PSI) - STANDARD**  
**DUTY**  
**EXCEEDS DIN 20018/1**



<b>TUBE</b>	BLACK SYNTHETIC ELASTOMER - OIL MIST RESISTANT
<b>REINFORCEMENT</b>	HIGH TENSILE TEXTILE CORDS
<b>COVER</b>	BLACK SYNTHETIC ELASTOMER WITH LONGITUDINAL YELLOW STRIPES - ABRASION AND OZONE RESISTANT
<b>APPLICATION</b>	COMPRESSED AIR AND GENERAL INDUSTRIAL APPLICATIONS.
<b>SAFETY FACTOR</b>	3:1
<b>TEMPERATURE</b>	-10°C +60°C (+14°F +140°F)
<b>BRAND TEXT</b>	ALFAGOMMA - ITALY - L-185 - 20 BAR (300 PSI) - AIR - dia mm -ggga
<b>BRAND TYPE</b>	EMBOSSSED
<b>APPROVALS</b>	
<b>NOTE</b>	

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
185AA0061311Y0	6	1/4	13	3,5	145	20	300		48	100	100
185AA0081511Y0	8	5/16	15	3,5	175	20	300		64	100	100
185AA0101711Y0	10	3/8	17	3,5	205	20	300		80	100	100
185AA0132111Y0	13	1/2	21	4	300	20	300		104	40/100	40/100
185AA0162511Y0	16	5/8	25	4,5	395	20	300		128	100	100
185AA0192911YZ	19	3/4	29	5	465	20	300		152	40/50/100	40/50/100
185AA0253611Y0	25	1"	35	5	640	20	300		200	40/50/100	40/50/100