






Global G2L PolarFlex® Hose - SAE 100R2 Type S
High Pressure

Continued

Description	Product No.						Standard Pack	Weight (Lbs.)
32G2LXCTN	4657-2316	2	2.62	1175	4700	25.0	120	2.15

J2AT 2-Wire Braid Jack Hose - 10,000 Static Pressure Only
High Pressure

Meets Flame Resistance Acceptance Designation "MSHA 2G"

Recommended For: Hydraulic jack applications. Meets Material Handling Institute specification IJ 100 for hydraulic hose and assemblies used with jacking systems. 10,000 Static Pressure Only

Tube: Black, oil resistant, synthetic rubber (Nitrile - Type C). See Hose Stock Characteristics.

Reinforcement: Two braids of high-tensile steel wire.






Cover: Black, oil and abrasion resistant, synthetic rubber (Nitrile/PVC - Type C2). Also available with unique abrasion resistant MegaTuff® cover. See Hose Stock Characteristics.

Temperature Range: -40°F to +120°F (-40°C to +49°C).

Coupling Recommendation (See gates.com/ecrimp or Crimp Data Manual 35019)

Use MegaCrimp® Male Pipe Long Nose Couplings on jack end of assembly for engagement. (Section G)



Description	Product No.						Standard Pack	Weight (Lbs.)
4J2AT X50FT	4657-4880	1/4	.59	10000	20000	2.0	1	13.45
4J2ATXREEL	4657-1400	1/4	.59	10000	20000	2.0	350	.27
6J2AT X50FT	4657-4881	3/8	.74	10000	20000	2.5	1	19.25
6J2ATXREEL	4657-1404	3/8	.74	10000	20000	2.5	330	.38

HOSE
HOSE/CPLG. SELECTION
G&K COUPLINGS
GLOBALSPIRAL COUPLINGS
PCM / PCS FERRULES
MEGACRIMP COUPLINGS
STAINLESS STEEL
POWER CRIMP COUPLINGS
LOC, GL AND GLP COUPLINGS
POLARSEAL COUPLINGS
POLARSEAL II COUPLINGS
C14 COUPLINGS
PCTS THERMOPLASTIC COUPLINGS
FIELD ATTACHABLE G1 & G2 COUPLINGS
FIELD ATTACHABLE C5 & C5E COUPLINGS
SURELOK AIR BRAKE COUPLINGS
ADAPTERS
QUICK DISCONNECT COUPLERS
LIVE SWIVEL
BALL VALVES
ACCESSORIES
EQUIPMENT AND PARTS