

GATES S-SERIES CHEMICAL HOSE <> SCH-150SD-HD (150 PSI)

Recommended For: Mandrel built rubber hose with compounded cross-linked polyethylene tube. It can handle a wide range of chemicals, petroleum products (including aromatics) and oils.

Temperature Range: -4°F to +185°F [-20°C to +85°C]

Tube: Translucent, smooth, cross-linked polyethylene

Reinforcement: High strength synthetic cord plus helix wire

Design Factor: 4:1

Cover: Green, EPDM rubber, higher resistance to weather, ozone and abrasion; above from 6" with corrugated cover for better flexibility

Branding: Continuous transfer. Example: "Gates SCH-150SD-HD CHEMICAL HOSE S.F. 4:1 150 PSI [10.3 Bar]"



PRODUCT CODE	ID (INCH)	OD (MM)	WP (PSI)	SAFETY FACTOR	LENGTH (FT)	COVER	LIST PRICE [US\$/FT]
12SCH-150SD-HD	3/4	32	150	4:1	200	GREEN	8.08
16SCH-150SD-HD	1	38	150	4:1	200	GREEN	9.15
20SCH-150SD-HD	1-1/4	45	150	4:1	200	GREEN	11.09
24SCH-150SD-HD	1-1/2	51	150	4:1	200	GREEN	12.43
32SCH-150SD-HD	2	65	150	4:1	200	GREEN	16.33
40SCH-150SD-HD	2-1/2	79	150	4:1	200	GREEN	22.34
48SCH-150SD-HD	3	91	150	4:1	200	GREEN	23.74
64SCH-150SD-HD	4	118	150	4:1	200	GREEN	33.32
80SCH-150SD-HD	5	148	150	4:1	200	GREEN	53.31
96SCH-150SD-HD	6	179	150	4:1	200	GREEN	70.56