

GATES S-SERIES PETROLEUM S&D HOSE <> SOL-150SD (150 PSI)

Recommended For: Low-pressure hydraulic oil fluids in suction lines or in low pressure in low pressure return lines.

Temperature Range: 13°F to +212°F [-25°C to +100°C]

Tube: Black NBR

Reinforcement: High strength textile fabric, with helix steel wire and anti-static copper wire

Design Factor: 3:1

Cover: Black, smooth (wrapped finish) CR/NBR blended rubber, flat

Branding: Continuous transfer. Example: "SOL-150SD PETROLEUM S&D HOSE 150 PSI [10.3 Bar]"



PRODUCT CODE	ID (INCH)	OD (MM)	WP (PSI)	SAFETY FACTOR	LENGTH (FT)	COVER	LIST PRICE [US\$/FT]
16SOL-150SD	1	38	150	3:1	200	BLACK	5.52
32SOL-150SD	2	65	150	3:1	200	BLACK	10.99
48SOL-150SD	3	90	150	3:1	200	BLACK	16.04
64SOL-150SD	4	116	150	3:1	200	BLACK	18.50
80SOL-150SD	5	143	150	3:1	200	BLACK	25.47
96SOL-150SD	6	178	150	3:1	200	BLACK	48.47
128SOL-150SD	8	231	150	3:1	100	BLACK	79.13
160SOL-150SD	10	284	150	3:1	100	BLACK	106.25
192SOL-150SD	12	339	150	3:1	39	BLACK	154.60