

850AA
FLEXOR 4SP MSHA
EN 856 4SP



Tube	OIL RESISTANT SYNTHETIC RUBBER
Reinforcement	FOUR HIGH TENSILE STEEL SPIRALS (4S)
Cover	ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER
Application	VERY HIGH PRESSURE HYDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER.
Constant operation	-40°C +100°C
Ambient temperature	-40°C +80°C
Fittings	Consult fittings catalogue
Length	Random
Branding	ALFAGOMMA FLEXOR 4SP/R9R -ID... WP ...MPa -(...PSI) - EN 856 4SP - DN... USMSHA IC-152/8 ... - Q/yr

Note

Code	ID mm	ID in	Dash	OD mm	OD in	WP Mpa	WP psi	BP Mpa	BP psi	BR mm	BR in	Weight kg/m	Weight lb/C ft
850AA00600PEB8	6	1/4	-4	17,9	0,7	45	6550	180	26200	150	6	0,58	39
850AA01000PEB8	10	3/8	-6	21,4	0,84	44,5	6450	178	25800	180	7,2	0,74	50
850AA01200PEB8	13	1/2	-8	24,6	0,97	41,5	6000	166	24000	230	9,2	0,88	59
850AA01600PEB8	16	5/8	-10	28,2	1,11	35	5000	140	20000	250	10	1,05	71
850AA02000PEB8	19	3/4	-12	32,2	1,27	38	5510	152	22040	300	12	1,44	96
850AA02500PEB8	25	1	-16	39,7	1,56	32	4640	128	18560	340	13,6	1,96	131