

Plaster**T-757 AA****PLASTER 40 BAR (600 PSI)**

TUBE	BLACK CONDUCTIVE NR - ABRASION RESISTANT
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS
COVER	BLACK CONDUCTIVE SBR/NR - ABRASION AND OZONE RESISTANT
APPLICATION	PLASTER PUMPING.
SAFETY FACTOR	2.5:1 CODES ENDING WITH "Z" 3:1
TEMPERATURE	-30°C +80°C (-22°F +176°F)
BRAND TEXT	ALFAGOMMA -ITALY- T-757 40 BAR (600 PSI) PLASTER (omega)
BRAND TYPE	WHITE LETTERS
APPROVALS	
NOTE	

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
757AA025387GE0	25	1"	38	6,5	720	40	600			30,5/40	40
757AA032467GE0	32	1" 1/4	46	7	900	40	600			30,5/40	40
757AA035497GE0	35	1" 3/8	49	7	990	40	600			40	40
757AA038547GE0	38	1" 1/2	54	8	1220	40	600			30,5/40	40
757AA051677GE0	51	2"	67	8	1650	40	600			30,5/40	40