

805AA
FLEXOR 5
SAE 100 R5



Tube	OIL RESISTANT SYNTHETIC RUBBER
Reinforcement	ONE HIGH TENSILE STEEL BRAID (1B)
Cover	BRAIDED HIGH TENSILE TEXTILE CORDS
Application	MEDIUM PRESSURE HYDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER.
Constant operation	-40°C +100°C (T max air = +70°C)
Ambient temperature	-40°C +80°C
Fittings	Consult fittings catalogue
Length	Random
Branding	ALFAGOMMA - FLEXOR 5 - ... ID ... - WP MPa (... PSI) - SAE 100 R5/J1402DOT All FM VSS... - Q/yr
Note	S.F.: 4:1

Code	ID mm	ID in	Dash	OD mm	OD in	WP Mpa	WP psi	BP Mpa	BP psi	BR mm	BR in	Weight kg/m	Weight lb/C ft
805AA005008CA8	5	3/16	-4	13,2	0,52	20,7	3000	83	12000	76	3	0,23	15
805AA006008CA8	6	1/4	-5	14,8	0,58	20,7	3000	83	12000	86	3,4	0,27	18
805AA008008CA8	8	5/16	-6	17,3	0,68	15,5	2250	62	9000	102	4,1	0,34	23
805AA011008CA8	10	13/32	-8	19,5	0,77	13,8	2000	55	8000	117	4,7	0,45	30
805AA012008CA8	13	1/2	-10	23,4	0,92	12,1	1750	48	7000	140	5,6	0,56	37
805AA016008CA8	16	5/8	-12	27,4	1,08	10,3	1500	41	6000	165	6,6	0,67	45
805AA022008CA8	22	7/8	-16	31,4	1,24	5,5	800	22	3200	187	7,5	0,69	46
805AA028008CA8	29	1.1/8	-20	38,1	1,5	4,3	625	17	2500	229	9,2	0,84	57
805AA035008CA8	35	1.3/8	-24	44,5	1,75	3,4	500	14	2000	267	10,7	1,06	71
805AA045008CA8	46	1.13/16	-32	56,4	2,22	2,4	350	10	1400	337	13,5	1,35	90