

**THERMOPLASTIC****8G1LA****FLEXOR 7****SAE 100 R7 - EN 855 R7**

<b>Tube</b>	THERMOPLASTIC POLYESTER
<b>Reinforcement</b>	Two high tensile textile braids and two tensile steel braids
<b>Cover</b>	ABRASION, OZONE AND HYDROCARBON RESISTANT THERMOPLASTIC POLYURETHANE-PIN PRICKED
<b>Application</b>	HIGH PRESSURE HYDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER.
<b>Constant operation</b>	-40°C +93°C
<b>Ambient temperature</b>	-40°C +80°C
<b>Fittings</b>	Consult fittings catalogue
<b>Length</b>	Random
<b>Branding</b>	
<b>Note</b>	S.F.: 4:1

Code	ID mm	ID in	Dash	OD mm	OD in	WP Mpa	WP psi	BP Mpa	BP psi	BR mm	BR in	Weight kg/m	Weight lb/C ft
8G1LA00400AG00	4	5/32		8,1	0,32	21	3000	84	12000	38	1,5	0,05	3
8G1LA00500AG00	5	3/16	-3	9,6	0,38	21	3000	84	12000	75	3	0,07	5
8G1LA00600AG00	6	1/4	-4	12,2	0,48	21	3000	84	12000	100	4	0,1	7
8G1LA00800AG00	8	5/16	-5	14,4	0,57	17,5	2500	70	10000	115	4,6	0,13	9
8G1LA01000AG00	10	3/8	-6	15,9	0,63	15,5	2250	62	9000	125	5	0,15	10
8G1LA01200AG00	13	1/2	-8	20,3	0,8	14	2000	56	8000	175	7	0,22	15