

## Hydrocarbons

## T-605 AA

## FUEL-OIL S&amp;D 10 BAR (150 PSI)



<b>TUBE</b>	BLACK CONDUCTIVE NBR
<b>REINFORCEMENT</b>	HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
<b>COVER</b>	BLACK CR - ABRASION, OZONE AND HYDROCARBON RESISTANT
<b>APPLICATION</b>	FUEL AND OIL SUCTION AND DELIVERY. SPECIALLY DESIGNED FOR TANK TRUCK AND GENERAL INDUSTRIAL APPLICATIONS.
<b>SAFETY FACTOR</b>	<=127mm 3:1 133-254mm 2.5:1 305mm 1.5:1
<b>TEMPERATURE</b>	-30°C +80°C (-22°F +176°F)
<b>BRAND TEXT</b>	ALFAGOMMA -ITALY- T-605 10 BAR (150 PSI) PETROLEUM S&D (omega)
<b>BRAND TYPE</b>	RED LETTERS
<b>APPROVALS</b>	
<b>NOTE</b>	

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
605AA019296MD0	19	3/4	29	5	600	10	150	100	76	20/30,5/61	30,5/61
605AA025356MD0	25	1"	35	5	740	10	150	100	100	20/30,5/61	30,5/61
605AA030406MD0	30	1" 3/16	40	5	840	10	150	100	120	30,5	30,5
605AA032426MD0	32	1" 1/4	42	5	900	10	150	100	128	20/30,5/61	30,5/61
605AA035456MD0	35	1" 3/8	45	5	960	10	150	100	140	30,5	30,5
605AA038486MD0	38	1" 1/2	48	5	1030	10	150	100	152	20/30,5/61	30,5/61
605AA040506MD0	40	1" 9/16	50	5	1070	10	150	100	160	30,5	30,5
605AA042526MD0	42	1" 5/8	52	5	1120	10	150	100	168	30,5	30,5
605AA045556MD0	45	1" 3/4	55	5	1190	10	150	100	180	30,5	30,5
605AA048586MD0	48	1" 7/8	58	5	1260	10	150	100	192	30,5	30,5
605AA051616MD0	51	2	61	5	1330	10	150	100	204	20/30,5/61	30,5/61
605AA057676MD0	57	2" 1/4	67	5	1460	10	150	100	228	20	
605AA060726MD0	60	2" 3/8	72	6	1990	10	150	100	240	30,5	30,5
605AA063756MD0	63	2" 1/2	75	6	2080	10	150	90	252	20/30,5	30,5
605AA070826MD0	70	2" 3/4	82	6	2300	10	150	90	280	30,5	30,5
605AA076886MD0	76	3"	88	6	2480	10	150	90	304	20/30,5	30,5
605AA080946MD0	80	3" 1/8	94	7	2660	10	150	90	320	30,5	30,5
605AA090046MD0	90	3" 1/2	104	7	3040	10	150	90	360	20/30,5	30,5
605AA102166MD0	102	4"	116	7	3400	10	150	90	408	20/30,5	30,5
605AA110246MD0	110	4" 5/16	124	7	4160	10	150	90	440	30,5	
605AA115296MD0	115	4" 1/2	129	7	4330	10	150	90	460	30,5	
605AA120386MD0	120	4" 3/4	138	9	5490	10	150	80	480	30,5	
605AA127456MD0	127	5"	145	9	5780	10	150	80	508	30,5	30,5
605AA133516MD0	133	5" 1/4	151	9	6030	10	150	80	532	30,5	30,5
605AA152706MD0	152	6"	170	9	7150	10	150	80	608	30,5	30,5
605AA160786MD0	160	6" 5/16	178	9	7490	10	150	80	640	30,5	30,5
605AA203256MD0	203	8"	225	11	11630	10	150	70	812	6,1	
605AA254766MD0	254	10"	276	11	15670	10	150	70	1016	6,1	
605AA305276MD0	305	12"	327	11	19940	10	150	70	1220	6,1	