

T-750 AA
SANDBLAST 10 BAR (150 PSI)


TUBE	BLACK CONDUCTIVE NR - ABRASION RESISTANT
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS
COVER	BLACK CONDUCTIVE SBR/NR - ABRASION AND OZONE RESISTANT - PIN PRICKED
APPLICATION	SANDBLAST.
SAFETY FACTOR	3:1
TEMPERATURE	-30°C +80°C (-22°F +176°F)
BRAND TEXT	ALFAGOMMA -ITALY- T-750 10 BAR (150 PSI) SANDBLAST (omega)
BRAND TYPE	WHITE LETTERS
APPROVALS	
NOTE	TOLERANCES ACCORDING TO "RMA" CLASS 311-A

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
750AA019337R03	19	3/4	33	7	670	10	150			30,5/40	40
750AA019357R03	19	3/4	35	8	790	10	150			40	
750AA019387R03	19	3/4	38	9,5	930	10	150			15,25/30,5/40	
750AA025407R03	25	1"	40	7,5	820	10	150			30,5/40	40
750AA025487R03	25	1"	48	11,5	1440	10	150			15,25/30,5/40	
750AA032487R03	32	1" 1/4	48	8	1180	10	150			30,5/40	40
750AA032557R03	32	1" 1/4	55	11,5	1730	10	150			15,25/30,5/40	
750AA038557R03	38	1" 1/2	55	8,5	1540	10	150			30,5/40	40
750AA038607R03	38	1" 1/2	60	11	1960	10	150			15,25/30,5/40	
750AA040607R03	40	1" 9/16	60	10	1810	10	150			40	40
750AA051717R03	51	2"	71	10	2210	10	150			30,5/40	40
750AA051737R03	51	2"	73	11	2490	10	150			15,25/30,5/40	