

**T-253 AA**  
**WATER DISCHARGE 10 BAR (150 PSI) - LAY**  
**FLAT**



<b>TUBE</b>	BLACK EPDM
<b>REINFORCEMENT</b>	HIGH TENSILE TEXTILE CORDS
<b>COVER</b>	BLACK EPDM - ABRASION AND OZONE RESISTANT
<b>APPLICATION</b>	LAY FLAT WATER DISCHARGE.
<b>SAFETY FACTOR</b>	3:1 >= 203mm 2:1
<b>TEMPERATURE</b>	-30°C +80°C (-22°F +176°F)
<b>BRAND TEXT</b>	ALFAGOMMA -ITALY- T-253 10 BAR (150 PSI) WATER DISCHARGE-EPDM
<b>BRAND TYPE</b>	GREEN LETTERS
<b>APPROVALS</b>	
<b>NOTE</b>	

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
253AA030382OJ0	30	1" 3/16	38	4	430	10	150			30,5	
253AA032402OJ0	32	1" 1/4	40	4	460	10	150			30,5	
253AA035432OJ0	35	1" 3/8	43	4	510	10	150			30,5	
253AA038462OJ0	38	1" 1/2	46	4	540	10	150			30,5	30,5
253AA040482OJ0	40	1" 9/16	48	4	570	10	150			30,5/61	61
253AA045532OJ0	45	1" 3/4	53	4	660	10	150			30,5/61	61
253AA051592OJ0	51	2"	59	4	730	10	150			30,5/61	30,5/61
253AA060682OJ0	60	2" 3/8	68	4	860	10	150			30,5	30,5
253AA063712OJ0	63	2" 1/2	71	4	890	10	150			30,5	30,5
253AA070782OJ0	70	2" 3/4	78	4	1190	10	150			30,5	30,5
253AA076842OJ0	76	3"	84	4	1280	10	150			30,5	30,5
253AA090982OJ0	90	3" 1/2	98	4	1490	10	150			30,5	30,5
253AA102102OJ0	102	4"	110	4	1770	10	150			30,5	30,5
253AA127372OJ0	127	5"	137	5	2400	10	150			30,5	
253AA152622OJ0	152	6"	162	5	2970	10	150			15,25/30,5	30,5
253AA203152OJ0	203	8"	215	6	4290	10	150			15,25/30,5	30,5