

ALFAGOMMA INDUSTRIAL

INDUSTRIAL HOSE DIVISION
ALFAGOMMA GROUP

TECHNICAL DATA SHEET
PETROL PUMP – STEEL BRAIDED

code: 6S8AA



APPLICATION:	GASOLINE AND DIESEL FUEL DISPENSING AND TRANSFER
TUBE:	BLACK CONDUCTIVE NBR
REINFORCEMENT:	HIGH TENSILE STEEL BRAID
COVER:	BLACK CONDUCTIVE CR – ABRASION, OZONE HYDROCARBON AND FIRE RESISTANT
WORKING TEMPERATURE:	-30°C +55°C (-22°F +131°F)
SAFETY FACTOR:	3:1
NORMS:	EN 1360/3: 2013 grade Ω

TECHNICAL DATA

INSIDE DIAMETER, mm:	16	19	25
OUTSIDE DIAMETER, mm	26	29	36
TOLERANCE ON OUTSIDE DIAMETER, mm	±0.8	±0.8	±1.2
MINIMUM BEND RADIUS, mm:	80	100	128
NOMINAL WEIGHT, kg/m:	0.470	0.520	0.720
MAXIMUM WORKING PRESSURE, bar:	16	16	16
ELECTRICAL RESISTANCE, Ω/length	<10 ⁶	<10 ⁶	<10 ⁶

ALFAGOMMA INDUSTRIAL S.p.A.

Cap. Soc. € 1.872.000,00 I.V. – REA Teramo N° 92225 – C. F. e P.IVA N° IT 00730430675

Registered Office, Administration and Plant/Sede legale, Amministrativa e Stabilimento: Nucleo Industriale – 64020 S. Atto (TE) ITALY – TEL. +39 0861.44.21 – FAX +39 0861.58.85.70

Sales/Commerciale: Via Torri Bianche, 1 – 20059 Vimercate (MI) ITALY – TEL. +39 039.60.16.1 – FAX +39 039.62.87.279

www.alfagomma.com e-mail: info@alfagomma.it