

## RLC 3-Fiber Braid Return Line and Low Pressure Hose

### Low Pressure

#### HOSE

HOSE/CPLG.  
SELECTION

**Recommended For:** Petroleum-base hydraulic oils, glycol antifreeze, air or water in low pressure fluid transfer or hydraulic system return lines. Generally connected to 100R4 stems, beaded nipples, or tube type ports with worm gear clamps.

G&K COUPLINGS

**Tube:** Black, oil resistant, synthetic rubber (Nitrile - Type C). See Hose Stock Characteristics.

GLOBALSPIRAL  
COUPLINGS

**Reinforcement:** Three fiber braids.

**Cover:** Black, oil and abrasion resistant, synthetic rubber (Modified Nitrile - Type C2). See Hose Stock Characteristics.

PCM / PCS  
FERRULES

**Temperature Range:** For hydraulic oil lines -40°F to +275°F (-40°C to +135°C); air to +160°F (+71°C) only. For water emulsions see Temperature Limits Table.



MEGACRIMP  
COUPLINGS

**Coupling Recommendation (See [gates.com/ecrimp](http://gates.com/ecrimp) or Crimp Data Manual 35019)**

Use barbed stem or beaded-tube with clamps only.

STAINLESS  
STEEL

POWER CRIMP  
COUPLINGS

Description	Product No.							Standard Pack	Weight (Lbs.)
16RLCXCTN	3319-0261	1	1.62	200	800	9.0	25	50	.75
20RLCXCTN	3319-0263	1 1/4	1.88	200	800	10.0	25	50	.88
24RLCXCTN	3319-0264	1 1/2	2.12	200	800	11.0	25	100	.95
28RLCXCTN	3319-0265	1 3/4	2.38	200	800	12.0	25	50	1.05
32RLCXCTN	3319-0266	2	2.56	200	800	13.0	25	50	1.30
36RLCXCTN	3319-0267	2 1/4	2.87	150	600	14.0	25	50	1.50
40RLCXCTN	3319-0268	2 1/2	3.12	150	600	16.0	25	50	1.81
48RLCXCTN	3319-0270	3	3.62	150	600	20.0	25	50	2.28
56RLCXCTN	3319-0272	3 1/2	4.12	150	600	24.0	25	50	2.58
72RLC X10FT	3319-0273	4 1/2	5.19	100	400	54.0	25	10	3.50

C14 COUPLINGS

PCTS  
THERMOPLASTIC  
COUPLINGS

FIELD  
ATTACHABLE G1  
& G2 COUPLINGS

FIELD  
ATTACHABLE C5  
& C5E  
COUPLINGS

SURELOK AIR  
BRAKE  
COUPLINGS

ADAPTERS

QUICK  
DISCONNECT  
COUPLERS

LIVE SWIVEL

BALL VALVES

ACCESSORIES

EQUIPMENT AND  
PARTS