

## Equipment



EQUIPMENT

HOSE/CPLG.  
SELECTION

GLOBALSPIRAL  
COUPLINGS

PCM/PCS  
FERRULES

MEGACRIMP  
COUPLINGS

POWER  
CRIMP  
COUPLINGS

LOW  
PRESSURE  
COUPLINGS

POLARSEAL  
COUPLINGS

C14  
COUPLINGS

PCTS  
THERMO-  
PLASTIC  
COUPLINGS

FIELD  
ATTACHABLE  
G1 & G2  
COUPLINGS

FIELD  
ATTACHABLE  
C5  
COUPLINGS

SURELOK AIR  
BRAKE  
COUPLINGS

QUICK  
DISCONNECT  
COUPLERS

NEW BALL  
VALVES

ACCESSORIES

EQUIPMENT  
AND PARTS



### SPECIFICATIONS

**Product Number:** 7480-0044

**Dimensions:** 10" wide by 10" deep by 25" high

**Weight:** 375 lbs.

**Production Rate:** 209 assemblies per hour (using 1/2" I.D. one-wire braid hose and straight stems with return stroke limiting arm).

## Power Crimp® 3000B

Crimp permanent assemblies in hose sizes from 3/16" through 2" I.D. (including six spiral-wire hose) using Gates Power Crimp 3000B.

Power Crimp 3000B is rugged enough to absorb the punishment of continued use. The ram can exert a hydraulic force in excess of 125 tons and can crimp all Gates hydraulic hose types from 3/16" through 2" I.D.

This Gates crimper uses an automatic limit switch to give push-button convenience during the crimping operation—accurately and dependably.

## Power Crimp® 3000B Die Selection Table

### For GlobalSpiral™ (G20) Couplings

Hose Sizes					
Hose Type	3/8"	1/2"	5/8"	3/4"	1"
G6K	33	33	35	35	37
G5K	33	33	35	35	37
C12M	33	33	—	35	37
					39

### For MegaCrimp® (G25) Couplings

Hose Sizes						
Hose Type	1/4"	3/8"	1/2"	5/8"	3/4"	1"
M3K	21 or 31	22 or 32	33	34	35	37
M2T	21 or 31	22 or 32	33	34	35	37
G1	21 or 31	22 or 32	33	34	35	37
G2	21 or 31	22 or 32	33	34	35	39

### For GSP & GSH Couplings

Hose Sizes		
Hose Type	1-1/2"	2"
EFG6K	311	—
EFG5K	311	314
EFG3K	311	313
G1H	310(L)	313
G2H	310(L)	312

For other hose and coupling configurations, reference [www.gates.com/ecrimp](http://www.gates.com/ecrimp) or Gates crimp data manual.

### Die Sets (ordered separately)

Die Set	21/31	22/32	33	34	35	37	39
Product No.	7482-1224/6515	7482-1225/6516	7482-6517	7482-6518	7482-6519	7482-6582	7482-7011
Die Set	310L①	311	312	313	314	32C4	
Product No.	7482-1127	7482-7023	7482-7029	7482-6523	7482-0298	7482-6584	

①310L supersedes 310 die.

## Power Crimp® 3000B Power Sources

### ELECTRO-HYDRAULIC PUMP SPECIFICATIONS

All Hydraulic Pumps Pressure Rating: 11,000 psi

**Product Number:** 7481-0013

440 Volt, 5 amp., 3 H.P., 3-Phase, 60 Cycles  
12-Quart Oil Capacity (20W)

**Product Number:** 7481-0014

230 Volt, 13 amp., 3 H.P., Single Phase,  
60 Cycles, 12-Quart Oil Capacity (20W)

Different voltage pumps are available  
on special order.

**Product Number:** 7481-0016

230 Volt, 10 amp., 3 H.P., 3-Phase,  
60 Cycles, 12-Quart Oil Capacity  
(20W)

**Product Number:** 7481-0026

115 Volt, 10 amp., 2 H.P., Single  
Phase, 60 Cycles, 8-Quart Oil  
Capacity (20W)



The World's Most Trusted Name in Belts, Hose and Hydraulics.

[www.gates.com/hydraulics](http://www.gates.com/hydraulics)

B5