

GATES S-SERIES SAND BLAST HOSE <> SSB-150 [150 PSI]

Recommended For: Room temperature, quartz sand transport, iron ore, cement, mud and other abrasive materials.

Temperature Range: -4°F to +185°F [-20°C to +85°C]

Tube: Black NR/BR/SBR

Reinforcement: High strength textile fabric

Design Factor: 3:1

Cover: Black, smooth [wrapped finish] NR/EPDM rubber, higher resistance to weather, ozone and abrasion

Branding: Continuous transfer. Example: "SSB-150 SAND BLAST HOSE 150 PSI [10.3 Bar]"



PRODUCT CODE	ID (INCH)	OD (MM)	WP (PSI)	SAFETY FACTOR	LENGTH (FT)	COVER	LIST PRICE [US\$/FT]
8SSB-150	1/2	20.5	150	3:1	328	BLACK	1.56
12SSB-150	3/4	32	150	3:1	200	BLACK	4.52
16SSB-150	1	38	150	3:1	200	BLACK	5.49
20SSB-150	1-1/4	46	150	3:1	200	BLACK	7.27
24SSB-150	1-1/2	52	150	3:1	200	BLACK	7.74
32SSB-150	2	66	150	3:1	200	BLACK	10.48
48SSB-150	3	91	150	3:1	200	BLACK	14.82
64SSB-150	4	122	150	3:1	200	BLACK	26.97
80SSB-150	5	147	150	3:1	200	BLACK	32.88
96SSB-150	6	172	150	3:1	200	BLACK	38.75