

GATES S-SERIES WATER S&D HOSE <> SWR-150SD (150 PSI)

Recommended For: Used in water transfer

Temperature Range: -4°F to +185°F [-20°C to +85°C]

Tube: Black NR/SBR blended

Reinforcement: High strength textile fabric+Helix wire

Design Factor: 3:1

Cover: Black NR/SBR or EPDM blended, Flat

Branding: Continuous transfer. Example: "SSWR-150SD WATER S&D HOSE 150 PSI [10.3 Bar]"



PRODUCT CODE	ID (INCH)	OD (MM)	WP (PSI)	SAFETY FACTOR	LENGTH (FT)	COVER	LIST PRICE (US\$/FT)
16SWR-150SD	1	38	150	3:1	200	BLACK	4.37
32SWR-150SD	2	64	150	3:1	200	BLACK	8.04
48SWR-150SD	3	90	150	3:1	200	BLACK	12.05
64SWR-150SD	4	121	150	3:1	200	BLACK	22.12
80SWR-150SD	5	146	150	3:1	200	BLACK	28.22
96SWR-150SD	6	177	150	3:1	200	BLACK	41.75
128SWR-150SD	8	229	150	3:1	100	BLACK	67.42
160SWR-150SD	10	284	150	3:1	100	BLACK	104.27
192SWR-150SD	12	338	150	3:1	39	BLACK	134.32