

TUC 20

Multi-Purpose Mineral Oil Hose



Applications:

Flexible delivery hose for suitable for mineral oil and fuels with maximum aromatic content of 40 % and compressed air.

Multi-purpose hose for diverse applications in industry, construction and agriculture.

For fuel application as a drop hose only.

Features:

Additional dimensions upon request.

Temperature range: -40 °C / +100 °C.

Safety factor: 3:1

Tube: Synthetic rubber, black, smooth, antistatic, oil resistant.

Reinforcement: Textile spiral construction.

Cover: Synthetic rubber, black, smooth, antistatic, abrasion

resistant, oil and weather resistant.

Identification: Continuous marking, white: "SEMPERIT S TUC

20 Öl/Luft Oil/Air PN 20 bar Antistatic MADE IN EU".

Article number	Inside Ø		Wall thickn.	Outside Ø	Work. pressure	No. of	Bending radius	Weight	Standard coil length
	mm	Inches	mm	mm	bar (max)	reinforce- ments	min. mm	approx. Kg/m	m
68112 0630	6,0	1/4	3,0	12,0	20	2	40	0,15	50
68112 0835	8,0	5/16	3,5	15,0	20	2	50	0,20	50
68112 1035	10,0	3/8	3,5	17,0	20	2	60	0,22	50
68112 1335	13,0	1/2	3,5	20,0	20	2	80	0,30	50
68112 1640	16,0	5/8	4,0	24,0	20	2	100	0,40	50
68112 1945	19,0	3/4	4,5	28,0	20	2	120	0,50	50
68112 2550	25,0	1	5,0	35,0	20	2	150	0,73	50